

## **Container Handler**

Used Container Handler Visalia - Container handlers, also known as cargo ships and container ships transport their load in a large intermodal container. Containerization is the shipping method that utilizes commercial freight transport to carry seagoing cargo in non-bulk sizes. The capacity of these specialty ships is equal to twenty-foot loads. Typical loads range with a mixture of 20-foot and 40-foot containers. Roughly 90% of non-bulk items all over the world travel via container ships. Container handlers are one of the biggest vessels sailing and are the main rival for oil tankers on the ocean. There are two main categories for dry cargo which are break-bulk and bulk cargo. Grain and coal fall into the bulk cargo category. They are often moved in their raw form, package-free in large volumes in the hull of the ship. Break-bulk cargo typically is made up of manufactured items that are shipped in packaging. Before the 1950s when containerization hadn't been invented yet, break-bulk materials were loaded, secured and unattached one piece at a time in a very time-consuming process. Grouping cargo into containers allows for 1000-3000 cubic feet of cargo to be simultaneously moved once every container has been secured with standardization techniques. Overall efficiency has largely increased with break-bulk cargo shipping. It is estimated that shipping time has been reduced by eighty-four percent and costs have been reduced by approximately thirtyfive percent. More than ninety percent of non-bulk items were recorded as being transported in containers in 2001. The first cargo ships were born in the 1940s as redesigns from World War II tankers. Container ships eliminate the individual holds, hatches and dividers normal within traditional cargo vessels. Essentially the container ship's hull is similar to a huge warehouse that uses vertical guide rails to divide it into cells. These cells have been designed to transport the cargo in containers. Most cargo ships are designed from steel but additional materials such as plywood, fiberglass and wood are used. Designed to be completely transferred to and from trains, semi-trailers, trucks, coastal carriers and more, there is a variety of container types that are categorized by their function and size. The entire shipping industry has been revolutionized by containerization, although, it did not start out in the easiest manner. At first, many companies and shippers were worried about the huge costs associated with constructing ports, railway infrastructure and the roads needed to transport items via cargo ships. Numerous trade unions were concerned that containers would affect port jobs and manual labor associated with cargo handling for dock and port workers. There was a decade of legal battles prior to the container ships starting international service. By 1966, after the first container liner service began from Rotterdam, Netherlands to the USA, cargo shipping was transformed. Loading and unloading of cargo ships has been reduced to a few hours instead of the days it used to take traditional cargo vessels. Along with cutting labor finances, it has shortened shipping times between ports to a large extent. Nowadays, it takes only weeks as opposed to months for items to be delivered from Europe to India and vice versa. Overall, there is less damaged cargo thanks to less physical handling and reduced cargo shifting due to properly securing loads. Containers are sealed prior to shipping and opened only once they arrive at their destination, resulting in less theft and disruption. There have been less shipping expenses and shipping time thanks to container ships which has increased international trade. Sealed factory containers now carry cargo that used to arrive in barrels, cartons, crates, bags and bales. Scanning machines work with computers to trace the product code on the contents. Amazingly, technology has advanced with this accurate tracking system to be so exact that a 2-week voyage can be timed for arrival with accuracy less than 15 minutes! Manufacturing times and delivery have been greatly enhanced with these advancements. Raw materials are delivered in less than an hour in sealed containers within an hour prior to being utilized for manufacturing. This results in more accuracy and less inventory costs. The shipping companies supply the exporters with boxes for loading products. They are delivered into the docks by rail or road or a combination of both to be loaded onto container ships. Containerization has streamlined the process of loading by reducing the number of workers and hours it takes to fit cargo into their holds. Cranes are used in the

shipping industry or on the pier to organize containers. After the hull has been fully loaded, additional containers can be attached to the deck. Efficiency has been one of the main design elements for cargo ships. Break-bulk ships may carry containers. However, cargo holds that have been dedicated to container ships have been carefully built to speed up the loading and unloading process and designed to keep containers secure while traveling the ocean. The specialized hatch design allows openings from the main deck to access the cargo holds. These openings are situated along the entire cargo hold breadth, surrounded by a raised steel structure called the hatch coaming. There are secure hatch covers situated on top of the hatch coamings. Wooden boards and tarps initially covered the hatches and held the battens secure until the 50s. Nowadays, solid metal plates comprise the hatch covers and cranes lift them onboard and off of the ship. Additional hatch models use hydraulic rams and articulated mechanisms for closing and opening. Another important cargo ship design feature is cell guides. These vertical structures are made of strong metal that is attached to the cargo hold on the ship. These guide the containers into certain locations and offer travel support on the high seas. Since the design of the container ship utilizes cell guides in such abundance, the UN Conference on Trade and Development relies on them to separate traditional break-bulk cargo ships and container ships. There are three dimensions used in cargo plans to determine the position of the container on board the ship. The initial coordinate starts at the beginning of the ship and increases aft. The second coordinate is the tier. The first tear begins in the lower portion of the cargo holds with the second tier found on top of the first tier and continuing in that fashion. The row is the third coordinate. Rows are situated on the ship's port side have even numbers while those found starboard have odd numbers. The cargo situated near the centerline showcases lower numbers and as the cargo increases further from the center, the numbers get higher. Container handlers carry 20, 40 and 45 foot containers. The largest size fits only above deck while the 40 foot size makes up for the majority of the load or approximately ninety percent of the container shipping. Roughly 90% of the freight in the world is delivered via container shipping. Approximately eighty-percent of global freight is shipped via forty-foot containers.